

WFS Transceivers – 10GbE Duplex & Bi-Directional SFPs and AOC

<u>WFS Part#s</u>	<u>Application</u>	<u>Form Factor</u>	<u>Data Rate</u>	<u>Reach</u>	<u>Wavelength</u>	<u>Transmitter</u>	<u>Receiver</u>	<u>Interface</u>	<u>Temperature</u>	<u>MaxLaunch Power dBm</u>	<u>Min Launch Power dBm</u>	<u>OverLoad dBm</u>	<u>Sensitivity dBm</u>
WFST-C96-02	10GBase-T	SFP+	10.3Gb/s	30m	NA	Copper	NA	RJ45	0-70 C	NA	NA	NA	NA
WFSP-8596-02	10GBase-SR	SFP+	10.3Gb/s	300m	850nm	VCSEL	PIN	LC	0-70 C	-1.0	-5.0	-1.0	-9.9
WFSP-1396-02M	10GBase-LRM	SFP+	10.3Gb/s	220m Multimode	1310nm	DFB	PIN	LC	0-70 C	0.5	-6.5	1.5	-10.0
WFSP-1396-10	10GBase-LR	SFP+	10.3Gb/s	10Km	1310nm	DFB	PIN	LC	0-70 C	0.5	-8.2	0.5	-14.4
WFSP-1396-40	10GBase-ER	SFP+	10.3Gb/s	40Km	1310nm	DFB	PIN	LC	0-70 C	5.0	0.0	0.5	-15.0
WFSP-1596-40	10GBase-ER	SFP+	10.3Gb/s	40Km	1550nm	EML	PIN	LC	0-70 C	4.0	-4.7	-1.0	-15.8
WFSP-1596-80	10GBase-ZR	SFP+	10.3Gb/s	80Km	1550nm	EML	APD	LC	0-70 C	4.0	0.0	-7.0	-24.0
WFSP-B273396-10 WFSP-B332796-10	10GBase-BX	SFP+	10.3Gb/s	10Km	1270nm Tx/ 1330nm Rx 1330nm Tx/ 1270nm Rx	DFB	PIN	LC	0-70 C	0.5	-8.2	0.5	-14.4
WFSP-B273396-40 WFSP-B332796-40	10GBase-BX	SFP+	10.3Gb/s	40Km	1270nm Tx/ 1330nm Rx 1330nm Tx/ 1270nm Rx	DFB	PIN	LC	0-70 C	6.0	0.5	0.5	-14.5
WFSP-B273396-60 WFSP-B332796-60	10GBase-BX	SFP+	10.3Gb/s	60Km	1270nm Tx/ 1330nm Rx 1330nm Tx/ 1270nm Rx	DFB	APD	LC	0-70 C	6.0	1.0	-8.0	-20.0
WFSP-B495596-80 WFSP-B554996-80	10GBase-BX	SFP+	10.3Gb/s	80Km	1490nm Tx/ 1550nm Rx 1550nm Tx/ 1490nm Rx	EML	APD	LC	0-70 C	4.0	-1.0	-6.0	-23.0
WFS-AOC-10G-xxM	10G AOC Lengths of 1-100m	SFP+	10.3Gb/s	1-100m	850nm	VCSEL	PIN	NA	0-70 C				